

LIF Class B2 Floodlighting Pear-Shaped Lamps

Code	Substitutes	Watts	Volts	Cap	Bulb	Finish	Filament	Type	Lumens	Colour	Life	Position	LCL	MOL	Source	Application	Notes
B2/1 HV		500	240	E40s	PS-130	Clear	C-5	I	7500		800	Any	202.0	275		Floodlighting	
B2/1 MV		500	115	E40s	PS-130	Clear	C-5	I	8250		800	Any	202.0	275		Floodlighting	
B2/2 HV		1,000	240	E40s	PS-150	Clear	C-5	I	16500		800	Any	225.0	309		Floodlighting	
B2/2 MV		1,000	115	E40s	PS-150	Clear	C-5	I	18000		800	Any	225.0	309		Floodlighting	
B2/3		1,500	240	E40s	PS-170	Clear	C-5	I	26250		800	Any	250.0	344		Floodlighting	
B2/4		2,000	240	P40s	PS-170	Clear	C-5	I	42000		200	Any	207.0	344		Floodlighting	
B2/5		1,000	240	E40s	PS-130	Clear	C-5	I	18000		800	Any	180.0	250		Floodlighting	
B2/6		1,000	240	E40s	PS-130	Clear	C-5	I	18000		800	Any	140.0	211		Floodlighting	
B2/7		1,500	240	E40s	PS-170	Clear	C-5	I	29000		800	Any	235.0	344		Floodlighting	
B2/8		1,500	240	P40s	PS-170	Clear	C-5	I	26000		800	Any	212.0	348		Floodlighting	