

## LIF Class K Halogen Floodlight Lamps

Code	Substitutes	Watts	Volts	Cap	Bulb	Finish	Filament	Type	Lumens	Colour	Life	Position	LCL	MOL	Source	Application	Notes
K/1 HV	BSH 64700	500	240	R7s-15	T-10.5	Clear	C-8 / CC-8	Q	9,500	2950K	2000	H ±15°	117.6	119.1		General lighting	
K/1 MV	FCL 64700	500	115	R7s-15	T-10.5	Clear	C-8 / CC-8	Q	10,500	3000K	2000	H ±15°	117.6	119.1		General lighting	LIF-coded FCL
K/2		750	240	R7s-15	T-10.5	Clear	C-8	Q	14500		2000	H ±15°		178.1		General lighting	
K/3	64560	750	240	R7s-15	T-10.5	Clear	C-8	Q	15000	3000K	2000	H ±15°		189.1		General lighting	
K/4 HV	64735/64740 (DZX)	1000	240	R7s-15	T-10.5	Clear	C-8	Q	21000	3050K	2000	H ±15°		189.1		General lighting	
K/4 MV	64735/64740 (DZX)	1000	115	R7s-15	T-10.5	Clear	C-8	Q	22000	3050K	2000	H ±15°		189.1		General lighting	
K/5	64760 (DYD)	1500	240	R7s-15	T-10.5	Clear	C-8	Q	33000	3050K	2000	H ±15°		254.1		General lighting	
K/6	64783	2000	240	Fa4	T-10.5	Clear	C-8	Q	44000	3100K	2000	H ±4°		334.4		General lighting	
K/7		10000	240	K28s	T-28	Clear	C-8	Q	255000	3200K	2000	H ±15°		665		General lighting	May be equipped with P28s cap
K/8	64784	2000	240	R7s-15	T-10.5	Clear	C-8	Q	44000		2000	H ±4°		330.8		General lighting	
K/9 HV	64701 (EHM)	300	240	R7s-15	T-10.5	Clear	C-8 / CC-8	Q	5000	2850K	2000	H ±15°	117.6	119.1		General lighting	
K/9 MV	EHM 64701	300	115	R7s-15	T-10.5	Clear	C-8 / CC-8	Q	5250	2900K	2000	H ±15°	117.6	119.1		General lighting	
K/9F		300	240	R7s-15	T-10.5	Frosted	C-8	Q	4950	2850	2000	H ±15°	117.6	119.1		General lighting	
K/10		1000	240	R7s-15	T-10.5	Clear	C-8	Q	21000		2000	H ±15°		254.1		General lighting	
K/11 HV	64698 (K/28 K/32)	200	240	R7s-15	T-10.5	Clear	CC-8	Q	3000	2900K	4000	Any	117.6	119.1		General lighting	
K/11 MV	64698 (K/28 K/32)	200	120	R7s-15	T-10.5	Clear	CC-8	Q	3200	2900K	4000	Any	117.6	119.1		General lighting	
K/12 HV	64695	150	240	R7s-15	T-10.5	Clear	CC-8	Q	2100	2800K	4000	Any	78.3	79.4		General lighting	
K/12 MV	64695	150	120	R7s-15	T-10.5	Clear	CC-8	Q	2300	2800K	4000	Any	78.3	79.4		General lighting	
K/13	M/150	150	240	E27s	T-28/32	Clear	CC-8	Q	2550		2000	Any	76	115		General lighting	Double jacket halogen lamp
K/13F	M/150P	150	240	E27s	T-28/32	Frosted	CC-8	Q	2450		2000	Any	76	115		General lighting	Double jacket halogen lamp
K/14 HV	64690	100	240	R7s-15	T-10.5	Clear	CC-8	Q	1300	2800K	4000	Any	78.3	79.4		General lighting	
K/14 MV	64690	100	120	R7s-15	T-10.5	Clear	CC-8	Q	1450	2800K	4000	Any	78.3	79.4		General lighting	
K/15	(K/27)	250	240	R7s-15	T-10.5	Clear	CC-8	Q	4000	2900K	2000	Any	78.3	79.4		General lighting	
K/16	M/182	100	240	E27s	T-28/32	Clear	CC-8	Q	1600		2000	Any	76	115		General lighting	Double jacket halogen lamp
K/16F	M/182P	100	240	E27s	T-28/32	Frosted	CC-8	Q	1525		2000	Any	76	115		General lighting	Double jacket halogen lamp
K/17		500	240	R7s-15	T-10.5	Clear	C-8	Q				H ±15°		189.1		General lighting	
K/18																General lighting	
K/19		100	240	E27s	BT-45	Clear	CC-8	Q	2550		2000	Any	76	115		General lighting	Double jacket halogen lamp
K/19O		100	240	E27s	BT-45	Opal	CC-8	Q	2327		2000	Any	76	115		General lighting	Double jacket halogen lamp
K/20		150	240	E27s	BT-45	Clear	CC-8	Q	1600		2000	Any	76	115		General lighting	Double jacket halogen lamp
K/20O		150	240	E27s	BT-45	Opal	CC-8	Q	1450		2000	Any	76	115		General lighting	Double jacket halogen lamp
K/21		100	120/240	B22d	T-32	Clear	CC-8	Q	1600		2000	Any	76	115		General lighting	Double jacket lamp
K/21F		100	120/240	B22d	T-32	Frosted	CC-8	Q	1525		2000	Any	76	115		General lighting	Double jacket lamp
K/22	64472BT	100	120/240	B22d	BT-45	Clear	CC-8	Q	1600		2000	Any	76	115		General lighting	Double jacket lamp
K/22O		100	120/240	B22d	BT-45	Opal	CC-8	Q	1450		2000	Any	76	115		General lighting	Double jacket lamp
K/23	M/183	75	240	E27s	T-32	Clear	CC-8	Q	1090		2000	Any	76	115		General lighting	Double jacket halogen lamp
K/23F	M/183P	75	240	E27s	T-32	Frosted	CC-8	Q	1040		2000	Any	76	115		General lighting	Double jacket halogen lamp
K/24		75	240	E27s	BT-45	Clear	CC-8	Q	1090		2000	Any	76	115		General lighting	Double jacket halogen lamp
K/24O		75	240	E27s	BT-45	Opal	CC-8	Q	990		2000	Any	76	115		General lighting	Double jacket halogen lamp
K/25		75	120/240	B22d	T-32	Clear	CC-8	Q	1090		2000	Any	76	115		General lighting	Double jacket lamp
K/25F		75	120/240	B22d	T-32	Frosted	CC-8	Q	1040		2000	Any	76	115		General lighting	Double jacket lamp
K/26		75	120/240	B22d	BT-45	Clear	CC-8	Q	1090		2000	Any	76	115		General lighting	Double jacket lamp
K/26O		75	120/240	B22d	BT-45	Opal	CC-8	Q	990		2000	Any	76	115		General lighting	Double jacket lamp
K/27 HV	(K/12)	200	240	R7s-15	T-10.5	Clear	CC-8	Q	3400	2850K	2000	Any	78.3	79.4		General lighting	
K/27 MV	(K/12)	200	120	R7s-15	T-10.5	Clear	CC-8	Q	2600	2850K	2000	Any	78.3	79.4		General lighting	
K/28 HV	(K/35 K/11)	150	240	R7s-15	T-10.5	Clear	CC-8	Q	2100	2850K	2000	H ±4°	117.6	119.1		General lighting	
K/28 MV	(K/35 K/11)	150	120	R7s-15	T-10.5	Clear	CC-8	Q	2300	2850K	2000	H ±4°	117.6	119.1		General lighting	
K/29		60	240	E27s	T-32	Clear	CC-8	Q			1500	Any	76	110		General lighting	Double jacket halogen lamp
K/29F		60	240	E27s	T-32	Frosted	CC-8	Q			1500	Any	76	110		General lighting	Double jacket halogen lamp

## LIF Class K Halogen Floodlight Lamps

Code	Substitutes	Watts	Volts	Cap	Bulb	Finish	Filament	Type	Lumens	Colour	Life	Position	LCL	MOL	Source	Application	Notes
K/30	64476BT	60	240	B22d	BT-45	Clear/Opal	CC-8	Q			1500	Any	76	115		General lighting	Double jacket lamp
K/31		60	240	E27s	BT-45	Clear	CC-8	Q			1500	Any	76	115		General lighting	Double jacket halogen lamp
K/31O		60	240	E27s	BT-45	Opal	CC-8	Q			1500	Any	76	115		General lighting	Double jacket halogen lamp
K/32	(K/11 K/9)	250	240	R7s-15	T-10.5	Clear	C-8	Q	4,000	2950K	2000	H ±4°	117.6	119.1		General lighting	
K/34	(K/14)	60	240	R7s-15	T-10.5	Clear	CC-8	Q	750	2750K	2000	Any	78.3	79.4		General lighting	
K/35 HV	(K/28)	100	240	R7s-15	T-10.5	Clear	CC-8	Q	1300	2800K	2000		117.6	119.1		General lighting	
K/35 MV	(K/28)	100	120	R7s-15	T-10.5	Clear	CC-8	Q	1450	2800K	2000		117.6	119.1		General lighting	