

LIF Class SL Railway Signal Lamps

| Code | Substitutes | Watts | Volts | Cap | Bulb | Finish | Filament | Type | Lumens | Colour | Life | Position | LCL | MOL | Source | Application | Notes |
|-------|-------------|---------|-------|--------|------|---------|----------|------|---------------|--------|------|----------|-------|------|-----------|----------------|--|
| SL/5 | | 4 | 12 | BA15d | G-38 | Clear | C-6 | I | | | | | 32 .5 | 56 4 | | Railway Signal | |
| SL/8 | | 6 | 12 | BA15d | G-38 | Clear | C-6 | I | | | | | 32 .5 | 56 4 | | Railway Signal | |
| SL/13 | | 12 | 6 | BA15d | G-38 | Clear | C-6 | I | | | | | 32 .5 | 56 4 | | Railway Signal | |
| SL/16 | | 12 | 12 | BA15d | P-38 | Clear | C-2R | I | 101 min. | | 1000 | | 32 .5 | 56 4 | 4.8 x 2.4 | Railway Signal | |
| SL/17 | | 25 | 12 | B22d-3 | G-50 | Clear | C-8/C-6 | I | 142 min. | | 1000 | | 42 .5 | 78 5 | | Railway Signal | Filament area 8.0x1.0 max (main) 1.0x8.0(aux.) |
| SL/18 | | 24 | 12 | B22d-3 | G-50 | Clear | C-6 | I | 260 min. | | 1000 | | 42 .5 | 73 5 | | Railway Signal | Filament area 10.1 x 1.0 max. |
| SL/21 | | 33 | 12 | B22d-3 | G-50 | Clear | C-8/C-6 | I | 218 min. | | 1000 | | 42 .5 | 78 5 | | Railway Signal | Filament area 8.0x1.0 max (main) 1.0x8.0(aux.) |
| SL/22 | | 14 | 12 | B22d-3 | G-50 | Clear | C-8/C-6 | I | 68 min. | | 1000 | | 42 .5 | 78 5 | | Railway Signal | Filament area 8.0x1.0 max (main) 1.0x8.0(aux.) |
| SL/25 | | 6 / 9 | 6 | BA15d | P-38 | Clear | C-8/C-2R | I | | | | | 32 .5 | 56 4 | | Railway Signal | |
| SL/28 | | 16 | 12 | BA15d | P-38 | Clear | C-6/C-2R | I | 114 min. | | 1000 | | 32 .5 | 56 4 | 4.8 x 2.4 | Railway Signal | Auxiliary filament 7.0 x 2.0 |
| SL/29 | | 2.4 | 12 | BA15d | G-38 | Clear | C-6 | I | | | | | 32 .5 | 56 4 | | Railway Signal | |
| SL/30 | | 1.2 | 12 | Side | | Red End | C-6 | I | | | | | | | | Railway Signal | |
| SL/32 | | 12 / 16 | 12 | BA15d | P-38 | Clear | C-6/C-2R | I | 9 / 166 min. | | 1000 | | 32 .5 | 56 4 | 4.8 x 2.4 | Railway Signal | Auxiliary filament 7.0 x 2.0 |
| SL/33 | | 25 | 110 | B22d-3 | G-50 | Clear | C-7A | I | 122 min. | | 1000 | | 42 .5 | 78 5 | | Railway Signal | Filament area 100 x 7.0 max. |
| SL/34 | | 16 / 24 | 12 | B22d-3 | G-50 | Clear | C-8/C-6 | I | 13 / 300 min. | | 1000 | | 42 .5 | 78 5 | | Railway Signal | Filament area 7.0x1.0 max (main) 1.0x7.0(aux.) |
| SL/35 | | 12 / 12 | 12 | B22d-3 | G-50 | Clear | C-8/C-6 | I | 50 / 260 min. | | 1000 | | 42 .5 | 78 5 | | Railway Signal | Filament area 7.0x1.0 max (main) 1.0x7.0(aux.) |