

Thorn Lighting - Class AF - Airfield Signal Lamps

Code	Substitutes	Watts	Volts	Cap	Bulb	Finish	Filament	Type	Lumens	Colour	Life	Position	LCL	MOL	Source	Application	Notes
AF1/1	J1/45 J1/42 ^Q	200	6.6A	P28s	T-45	Clear	CC-8	I	4,500		300	VBD	55.5	135		Airfield	
AF1/2	J1/53 (EL60)	200	8.33A	P28s	G-80	Clear	C-13	I	3,700		200	VBD ±90°	55.5	130		Airfield	
AF1/3	J1/33 EL50	100	8.33A	BA20s	P-60	Clear	C-2	I	2100		50	VBD ±90°	43	93		Airfield	
AF1/4	J1/61 EL50TH	100	8.33A	BA20s	T-10.5	Clear	C-8	Q	2100		750	VBD ±90°	43	80		Airfield	
AF2/1	J1/48 EL55 J1/42 ^Q	200	6.6A	P28s	P-80	Clear	CC-8	I	3,700		200	VBD ±135°	55.5	130		Airfield	
AF2/2	1/52 EL/39 EL60 J1/50	200	8.33A	P28s	P-80	Clear	CC-8	I	3,700		200	VBD ±135°	55.5	130		Airfield	
AF3/1	J1/35 EL56	100	8.33A	P28s	P-60	Clear	CC-6	I	2300		50	VBD	55.5	112		Airfield	
AF3/2	J1/29 EL57	100	8.33A	P30s	T-32	Clear	CC-6	I	2100		50	VBD	28.5	90		Airfield	
AF3/3	J1/41 EL63	200	6.6A	P30s	T-32	Clear	CC-8	I	4600		100	VBD	30	90		Airfield	
AF4/1	J1/1	30	6.6A	BA20s	P-38	Clear	C-8	I	390		50	VBD	30	69		Airfield	
AF4/2	J1/15	45	6.6A	BA20s	P-38	Clear	C-8	I	585		1000	VBD	30	69		Airfield	Long Life version of AF4/3
AF4/3	J1/7 EL40	36	6.0A	BA20s	P-38	Clear	C-8	I	560		100	VBD	30	69		Airfield	High output version of AF4/2
AF4/4	J1/8 EL52	36	6.0A	BA20s	P-60	Clear	C-8	I	575		50	VBD ±90°	43	95		Airfield	
AF5/1	EL36 AF5/5 ^Q J1/60 ^Q EL	36	6.0A	B15d	G-38	Clear	C-2V	I	570		100	Any	28.5	58		Airfield	
AF5/2	J1/18 EL33	60	6.6A	P28s	T-64	Clear	C-2V	I	1,100		50		65	125		Airfield	
AF5/4	J1/62	36	6.0A	G6.35	T-10.5	Clear	C-8	Q	610		600	VBD ±90°	30.5	42		Airfield	
AF5/5	EL36TH AF5/1 ^I J1/6 ^I	36	6.0A	BA15d	T-10.5	Clear	C-8	Q	610		750	Any	28.5	48		Airfield	
AF6/1	J1/9	45	6.6A	G6.35	T-12	Clear	C-6	Q	750		600	Any	25	35		Airfield	
AF6/2	J1/10	45	6.6A	PG22d	T-12	Clear	C-6	Q	800		600	VBD ±90°	21	49.75		Airfield	
AF6/5	J1/21 J1/70	100	6.6A	PG22d	T-12	Clear	FC-8	Q	2100		600	VBD ±90°	22.15	58.75		Airfield	
AF6/5E	J1/21	100	6.6A	PG22d	T-12	Half frosted	FC-8	Q	2100		600	VBD ±90°	22.15	58.75		Airfield	Etched on one side of bulb
AF7/2	J1/37	200	6.6A	PG22d	T-12	Clear	FC-8	Q	4800		600	VBD ±90°	24	54		Airfield	
AF9/2	J1/63	200	6.6A	¼" Spade	PAR-64	Clear	C-6	I	. . .		1000	Horiz.	N/A	89	VNSP	Airfield	Sealed Beam Glide Approach Path Indicator
AF9/3	J1/54 EL61	200	16.6A	¼" Spade	PAR-64	Clear	C-6	I	. . .		1000	Horiz.	N/A	89	VNSP	Airfield	Sealed Beam Glide Approach Path Indicator
AF11/1	J1/64	65	240V	E27s	PS-60	Clear	C-7A	I	510		1000	Any	65	110		Airfield Traffic Signal	